

Sand Equivalent Value

EN 933-8; ASTM D2419; AASHTO T176

Set Includes:-

- 4 Plastic measuring cylinders
- 1 Carrying case
- 1 Weighted foot assembly
- 1 Irrigator tube
- 1 Rubber tubing complete with pinch clip
- 1 Funnel

EL24-4915 Sand Equivalent Apparatus



Left: EL24-4950/01. Right: EL24-4945/01



Ordering Information

EL24-4915
Sand Equivalent Apparatus EN 933-8

EL24-4919
Sand Equivalent Apparatus ASTM D2419

Accessories

EL24-4925 **Syphon Assembly** with 5 litre polythene bottle. Supplied without rubber tubing.

EL24-4930 **Calcium Chloride** 2.5 kg.

EL24-4932 **Formaldehyde** 40% solution, 2.5 litres.

EL24-4934 **Glycerol Analar** 2.5 litres.

Spares

EL24-4915/15 **Plastic Measuring Cylinder** dual graduations suitable for EN and ASTM test methods.

Mechanical Sand Equivalent Shaker

Recommended for use in laboratories performing a large number of tests, these shakers provides a consistent and repeatable oscillation, minimising variation in test results.

Ordering Information

EL24-4945/01
Mechanical Sand Equivalent Shaker ASTM Method.

Weight 32.0 kg
For 220 – 240 V AC, 50 – 60 Hz, 1 ph

EL24-4950/01
Motorised Sand Equivalent Shaker with Interlock Guard,

EN Method. Weight 30.0 kg
For 220 – 240V, 50 Hz, 1ph